

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

REPORT ID: 6A7C37EF-8DE60618-4B4357
TIMESTAMP: 12.8.2026, 11:07
SOURCE CATEGORY: Line In (iSV1611 Instrumentation)
ANALYSIS MODE: LIVE SOURCE

METROLOGY CONFIGURATION SNAPSHOT

SAMPLE RATE: 48.0 kHz
ADC CEILING: 0.17 V
SENSITIVITY: 47.00 mV/Pa
OFFSET: +0.0 dB
MAX AMPLITUDE: 100.4 dB

LABORATORY SPECTRAL TELEMETRY

UNCERTAINTY DISCLOSURE: NIST-Traceable Adaptive Quantization Limits ± 0.146 Hz to ± 0.73 Hz.
Reported values reflect Dynamic FFT Bin Centers based on band-specific frequency resolution @ 48.0kHz.

BAND	CAT. LIMITS	DETECTED RANGE	NIST PEAK
DELTA	0.5-4.0Hz	0.6-3.8Hz	1.46 Hz
THETA	4.0-8.0Hz	3.8-7.9Hz	7.62 Hz
ALPHA	8.0-12.0Hz	7.9-11.7Hz	7.91 Hz
BETA	12.0-30.0Hz	11.7-29.9Hz	12.01 Hz
GAMMA	30.0-100.0Hz	29.3-99.6Hz	99.61 Hz

DETECTION CHRONOLOGY (TIMECODE BREAKDOWN)

TIME	BAND	SIGNAL	INTENSITY
11:01:10.84	SIGNAL	29.30 Hz	42.8 dB
11:01:11.19	SIGNAL	42.48 Hz	43.8 dB
11:01:11.73	ALPHA	9.67 Hz	61.6 dB
11:01:11.73	ALPHA	10.55 Hz	61.6 dB
11:01:11.92	ALPHA	10.25 Hz	52.6 dB
11:01:12.26	ALPHA	9.96 Hz	52.5 dB
11:01:12.42	ALPHA	9.67 Hz	47.6 dB
11:01:12.93	ALPHA	10.84 Hz	48.2 dB
11:01:13.11	ALPHA	9.96 Hz	48.0 dB
11:01:14.30	ALPHA	11.13 Hz	46.8 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025-2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

TIME	BAND	SIGNAL	INTENSITY
11:01:14.47	ALPHA	9.96 Hz	45.4 dB
11:01:15.15	DELTA	1.17 Hz	43.5 dB
11:01:16.17	DELTA	1.46 Hz	47.2 dB
11:01:17.36	DELTA	1.17 Hz	47.9 dB
11:01:20.45	DELTA	1.46 Hz	44.9 dB
11:01:21.80	GAMMA	67.38 Hz	69.6 dB
11:01:30.99	GAMMA	99.61 Hz	78.7 dB
11:01:36.79	GAMMA	49.80 Hz	84.4 dB
11:01:36.97	GAMMA	99.61 Hz	80.2 dB
11:01:54.38	GAMMA	96.68 Hz	48.7 dB
11:01:54.54	GAMMA	99.61 Hz	42.2 dB
11:01:55.08	DELTA	1.76 Hz	46.6 dB
11:01:55.59	DELTA	1.46 Hz	48.3 dB
11:01:55.94	DELTA	0.88 Hz	45.7 dB
11:01:56.28	DELTA	0.59 Hz	40.6 dB
11:01:57.13	GAMMA	99.61 Hz	78.7 dB
11:02:01.19	GAMMA	89.36 Hz	76.8 dB
11:02:02.73	GAMMA	80.57 Hz	74.3 dB
11:02:04.09	GAMMA	70.31 Hz	71.1 dB
11:02:05.47	GAMMA	60.06 Hz	66.0 dB
11:02:06.83	GAMMA	49.80 Hz	61.2 dB
11:02:08.53	GAMMA	41.02 Hz	60.3 dB
11:02:08.71	GAMMA	39.55 Hz	60.5 dB
11:02:11.77	GAMMA	30.76 Hz	61.9 dB
11:02:11.95	GAMMA	29.30 Hz	61.4 dB
11:02:18.60	GAMMA	30.76 Hz	58.2 dB
11:02:18.79	GAMMA	99.61 Hz	57.5 dB
11:02:18.82	BETA	29.88 Hz	56.8 dB
11:02:20.01	BETA	19.92 Hz	56.8 dB
11:02:32.81	DELTA	1.17 Hz	46.4 dB
11:02:34.84	ALPHA	9.96 Hz	44.8 dB
11:02:39.45	DELTA	1.46 Hz	45.4 dB
11:02:39.45	ALPHA	9.96 Hz	45.4 dB
11:02:39.60	DELTA	0.59 Hz	50.1 dB
11:02:39.60	DELTA	0.88 Hz	50.1 dB
11:02:40.83	DELTA	1.46 Hz	46.0 dB
11:02:41.18	ALPHA	9.96 Hz	48.6 dB
11:02:42.18	ALPHA	10.25 Hz	49.6 dB
11:02:42.88	DELTA	1.76 Hz	47.1 dB
11:02:43.22	DELTA	0.88 Hz	45.4 dB
11:02:43.88	DELTA	1.17 Hz	46.4 dB
11:02:44.57	DELTA	0.88 Hz	49.6 dB
11:02:46.81	DELTA	0.59 Hz	50.3 dB
11:02:48.17	DELTA	0.88 Hz	47.3 dB
11:02:49.37	DELTA	2.05 Hz	51.3 dB
11:02:49.71	DELTA	0.88 Hz	43.6 dB
11:02:52.95	DELTA	1.17 Hz	49.3 dB
11:02:53.62	DELTA	1.76 Hz	47.8 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025–2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

TIME	BAND	SIGNAL	INTENSITY
11:02:54.31	THETA	4.98 Hz	44.6 dB
11:02:56.20	DELTA	0.59 Hz	50.2 dB
11:02:56.20	DELTA	2.64 Hz	50.2 dB
11:02:56.70	DELTA	2.05 Hz	48.0 dB
11:02:57.20	DELTA	2.64 Hz	51.8 dB
11:02:57.39	DELTA	3.52 Hz	51.9 dB
11:02:57.71	DELTA	3.81 Hz	58.5 dB
11:02:59.44	THETA	4.10 Hz	48.4 dB
11:02:59.73	THETA	4.69 Hz	40.5 dB
11:03:00.10	THETA	4.98 Hz	46.0 dB
11:03:01.64	DELTA	0.59 Hz	44.7 dB
11:03:03.00	DELTA	1.46 Hz	45.4 dB
11:03:03.87	DELTA	1.17 Hz	46.2 dB
11:03:04.70	DELTA	0.88 Hz	42.6 dB
11:03:06.94	DELTA	1.17 Hz	44.7 dB
11:03:09.67	SIGNAL	1.46 Hz	43.4 dB
11:03:16.15	DELTA	1.76 Hz	52.8 dB
11:03:17.35	DELTA	1.46 Hz	47.4 dB
11:03:18.21	DELTA	1.17 Hz	48.0 dB
11:03:20.06	DELTA	1.46 Hz	44.9 dB
11:03:22.14	DELTA	0.88 Hz	52.9 dB
11:03:24.35	DELTA	1.17 Hz	36.0 dB
11:03:26.05	DELTA	1.76 Hz	41.2 dB
11:03:27.24	DELTA	1.46 Hz	35.9 dB
11:03:28.44	DELTA	1.17 Hz	42.0 dB
11:03:29.80	DELTA	1.76 Hz	44.5 dB
11:03:30.14	DELTA	1.46 Hz	46.5 dB
11:03:32.53	BETA	19.92 Hz	65.1 dB
11:04:24.58	DELTA	1.17 Hz	68.6 dB
11:04:24.58	DELTA	0.88 Hz	68.6 dB
11:04:25.78	DELTA	1.17 Hz	71.7 dB
11:04:27.82	DELTA	0.88 Hz	69.9 dB
11:04:29.37	DELTA	1.17 Hz	68.7 dB
11:04:30.22	DELTA	0.88 Hz	66.2 dB
11:04:41.65	DELTA	1.17 Hz	66.8 dB
11:04:43.03	DELTA	0.88 Hz	77.1 dB
11:04:44.57	BETA	19.92 Hz	65.4 dB
11:04:44.57	DELTA	0.88 Hz	65.4 dB
11:04:48.14	BETA	19.92 Hz	65.2 dB
11:04:52.92	DELTA	0.88 Hz	65.2 dB
11:04:52.92	BETA	19.92 Hz	65.2 dB
11:05:41.91	GAMMA	41.02 Hz	73.9 dB
11:05:42.03	GAMMA	48.34 Hz	73.9 dB
11:05:42.22	GAMMA	60.06 Hz	74.9 dB
11:05:42.54	GAMMA	70.31 Hz	78.8 dB
11:05:43.23	GAMMA	80.57 Hz	82.0 dB
11:05:43.58	GAMMA	89.36 Hz	84.2 dB
11:05:44.77	GAMMA	90.82 Hz	86.1 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025-2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

TIME	BAND	SIGNAL	INTENSITY
11:05:44.93	GAMMA	99.61 Hz	86.0 dB
11:05:52.96	GAMMA	95.21 Hz	45.3 dB
11:05:53.47	GAMMA	52.73 Hz	43.4 dB
11:05:54.03	DELTA	0.88 Hz	41.5 dB
11:05:55.23	DELTA	1.46 Hz	40.8 dB
11:05:55.54	DELTA	0.88 Hz	43.6 dB
11:05:56.08	DELTA	1.17 Hz	45.3 dB
11:05:56.39	DELTA	0.88 Hz	44.7 dB
11:05:57.43	DELTA	1.46 Hz	48.0 dB
11:05:58.29	DELTA	1.17 Hz	50.9 dB
11:05:59.32	DELTA	0.88 Hz	43.6 dB
11:06:00.33	DELTA	1.76 Hz	47.1 dB
11:06:01.37	DELTA	0.59 Hz	42.1 dB
11:06:02.03	DELTA	0.88 Hz	48.6 dB
11:06:03.92	DELTA	1.76 Hz	46.5 dB
11:06:04.43	DELTA	1.46 Hz	47.1 dB
11:06:05.12	DELTA	1.17 Hz	51.1 dB
11:06:05.62	DELTA	0.88 Hz	52.2 dB
11:06:06.66	DELTA	1.17 Hz	62.2 dB
11:06:07.86	DELTA	3.22 Hz	76.9 dB
11:06:08.18	ALPHA	10.84 Hz	70.5 dB
11:06:10.75	DELTA	1.17 Hz	42.4 dB
11:06:11.60	DELTA	1.46 Hz	50.6 dB
11:06:12.45	DELTA	1.76 Hz	49.9 dB
11:06:13.49	DELTA	2.05 Hz	45.5 dB
11:06:14.00	DELTA	0.88 Hz	87.7 dB
11:06:14.16	DELTA	1.76 Hz	100.4 dB
11:06:14.34	DELTA	2.34 Hz	99.9 dB
11:06:16.70	DELTA	1.46 Hz	75.4 dB
11:06:17.55	THETA	7.62 Hz	68.4 dB
11:06:18.79	THETA	7.32 Hz	62.6 dB
11:06:20.99	THETA	7.62 Hz	67.2 dB
11:06:21.68	THETA	7.91 Hz	72.1 dB
11:06:22.53	DELTA	1.46 Hz	66.1 dB
11:06:22.68	THETA	7.91 Hz	65.5 dB
11:06:22.68	DELTA	1.46 Hz	65.5 dB
11:06:23.73	DELTA	2.05 Hz	62.4 dB
11:06:24.73	DELTA	1.76 Hz	54.2 dB
11:06:25.59	DELTA	1.46 Hz	71.5 dB
11:06:25.92	DELTA	2.05 Hz	70.6 dB
11:06:26.78	DELTA	0.88 Hz	71.4 dB
11:06:27.13	DELTA	0.59 Hz	54.2 dB
11:06:27.31	THETA	7.91 Hz	56.5 dB
11:06:27.31	THETA	7.62 Hz	56.5 dB
11:06:28.67	DELTA	1.46 Hz	65.5 dB
11:06:29.52	DELTA	1.76 Hz	69.2 dB
11:06:30.55	DELTA	2.05 Hz	72.6 dB
11:06:30.71	ALPHA	8.20 Hz	72.8 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025–2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

TIME	BAND	SIGNAL	INTENSITY
11:06:30.71	DELTA	2.05 Hz	72.8 dB
11:06:31.22	DELTA	1.46 Hz	72.5 dB
11:06:32.07	DELTA	1.17 Hz	72.9 dB
11:06:32.76	GAMMA	43.95 Hz	68.6 dB
11:06:32.89	GAMMA	99.61 Hz	68.6 dB
11:06:33.23	GAMMA	96.68 Hz	65.3 dB
11:06:33.61	DELTA	3.52 Hz	70.6 dB
11:06:33.61	DELTA	3.81 Hz	70.6 dB
11:06:34.80	THETA	7.91 Hz	52.6 dB
11:06:34.96	DELTA	3.81 Hz	51.9 dB
11:06:34.96	THETA	7.91 Hz	51.9 dB
11:06:35.30	THETA	7.62 Hz	57.1 dB
11:06:37.55	DELTA	1.17 Hz	48.2 dB
11:06:38.05	DELTA	0.88 Hz	47.9 dB
11:06:38.21	DELTA	1.76 Hz	47.9 dB
11:06:38.90	DELTA	1.46 Hz	48.0 dB
11:06:39.75	DELTA	2.05 Hz	45.4 dB
11:06:41.13	DELTA	1.76 Hz	44.8 dB
11:06:44.19	DELTA	1.46 Hz	48.1 dB
11:06:46.07	DELTA	1.76 Hz	55.2 dB
11:06:47.78	THETA	7.03 Hz	41.4 dB
11:06:48.13	THETA	7.32 Hz	45.0 dB
11:06:48.63	THETA	7.62 Hz	43.9 dB
11:06:49.48	ALPHA	11.43 Hz	43.1 dB
11:06:49.48	THETA	7.62 Hz	43.1 dB
11:06:49.66	ALPHA	8.20 Hz	44.9 dB
11:06:50.67	GAMMA	99.61 Hz	55.9 dB
11:06:50.83	GAMMA	98.14 Hz	55.9 dB
11:06:51.68	GAMMA	45.41 Hz	44.9 dB
11:06:51.84	GAMMA	43.95 Hz	50.8 dB
11:06:52.56	DELTA	0.88 Hz	57.1 dB
11:06:52.56	DELTA	1.46 Hz	57.1 dB
11:06:53.41	THETA	7.91 Hz	57.8 dB
11:06:53.57	DELTA	1.46 Hz	57.7 dB
11:06:55.62	THETA	7.91 Hz	62.9 dB
11:06:57.51	ALPHA	9.38 Hz	65.2 dB
11:06:58.86	ALPHA	9.67 Hz	57.8 dB
11:07:00.40	ALPHA	9.96 Hz	64.8 dB
11:07:01.27	ALPHA	7.91 Hz	66.4 dB
11:07:01.45	THETA	7.62 Hz	62.6 dB
11:07:01.45	ALPHA	7.91 Hz	62.6 dB
11:07:01.60	THETA	7.62 Hz	61.7 dB
11:07:03.15	THETA	7.32 Hz	64.9 dB
11:07:05.01	THETA	7.62 Hz	63.2 dB
11:07:07.93	THETA	7.91 Hz	61.3 dB
11:07:08.43	THETA	7.62 Hz	60.0 dB
11:07:08.59	ALPHA	8.20 Hz	59.7 dB
11:07:08.94	ALPHA	8.79 Hz	61.8 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025–2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

TIME	BAND	SIGNAL	INTENSITY
11:07:09.64	ALPHA	9.38 Hz	53.8 dB
11:07:10.30	ALPHA	9.67 Hz	55.5 dB
11:07:11.50	ALPHA	7.91 Hz	51.7 dB
11:07:12.37	ALPHA	8.20 Hz	47.1 dB
11:07:12.69	ALPHA	8.50 Hz	55.4 dB
11:07:13.54	ALPHA	9.67 Hz	45.4 dB
11:07:13.85	ALPHA	11.72 Hz	48.8 dB
11:07:14.06	DELTA	0.59 Hz	48.3 dB
11:07:15.42	DELTA	1.46 Hz	47.6 dB
11:07:16.62	DELTA	1.17 Hz	50.6 dB
11:07:21.56	GAMMA	74.71 Hz	54.4 dB
11:07:21.88	GAMMA	62.99 Hz	53.2 dB
11:07:22.41	ALPHA	7.91 Hz	48.2 dB
11:07:23.46	ALPHA	8.20 Hz	46.7 dB
11:07:26.50	ALPHA	7.91 Hz	44.5 dB
11:07:26.69	THETA	7.62 Hz	47.9 dB
11:07:26.69	ALPHA	7.91 Hz	47.9 dB
11:07:26.82	THETA	7.62 Hz	50.2 dB
11:07:28.73	DELTA	1.46 Hz	47.7 dB
11:07:30.59	DELTA	1.17 Hz	54.8 dB
11:07:30.93	THETA	7.91 Hz	65.4 dB
11:07:31.12	GAMMA	79.10 Hz	60.3 dB
11:07:31.24	GAMMA	77.64 Hz	60.3 dB
11:07:31.75	GAMMA	79.10 Hz	59.1 dB
11:07:32.13	DELTA	1.17 Hz	58.4 dB
11:07:32.44	GAMMA	43.95 Hz	59.6 dB
11:07:32.94	GAMMA	45.41 Hz	66.6 dB
11:07:33.13	GAMMA	43.95 Hz	57.3 dB
11:07:33.63	GAMMA	45.41 Hz	62.1 dB
11:07:34.01	DELTA	1.76 Hz	63.8 dB
11:07:35.02	THETA	7.32 Hz	65.1 dB
11:07:35.21	DELTA	1.76 Hz	64.0 dB
11:07:35.21	THETA	7.32 Hz	64.0 dB
11:07:35.71	THETA	7.62 Hz	62.8 dB
11:07:36.40	THETA	7.32 Hz	63.0 dB
11:07:37.26	THETA	7.03 Hz	55.7 dB
11:07:37.41	THETA	6.74 Hz	64.3 dB
11:07:37.75	DELTA	3.52 Hz	63.8 dB
11:07:37.75	DELTA	1.76 Hz	63.8 dB
11:07:38.59	DELTA	2.05 Hz	64.7 dB
11:07:38.92	DELTA	3.22 Hz	94.9 dB
11:07:39.30	DELTA	1.46 Hz	86.9 dB
11:07:42.03	THETA	4.39 Hz	59.7 dB
11:07:42.03	DELTA	1.46 Hz	59.7 dB
11:07:42.03	DELTA	1.17 Hz	59.7 dB
11:07:42.20	THETA	4.39 Hz	61.1 dB
11:07:42.20	DELTA	1.17 Hz	61.1 dB
11:07:42.35	THETA	3.81 Hz	58.7 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025–2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).

FreqCheck™

FREQUENCY AUDIT REPORT | IND CORE™ TECHNOLOGY

TIME	BAND	SIGNAL	INTENSITY
11:07:42.35	DELTA	1.17 Hz	58.7 dB
11:07:42.35	DELTA	0.88 Hz	58.7 dB
11:07:42.54	THETA	3.81 Hz	61.2 dB
11:07:42.54	DELTA	0.88 Hz	61.2 dB
11:07:42.70	THETA	3.81 Hz	59.7 dB
11:07:42.70	DELTA	0.88 Hz	59.7 dB
11:07:42.88	THETA	3.81 Hz	57.9 dB
11:07:42.88	DELTA	0.88 Hz	57.9 dB
11:07:42.88	DELTA	3.81 Hz	57.9 dB
11:07:43.05	THETA	5.27 Hz	61.1 dB
11:07:43.05	DELTA	3.81 Hz	61.1 dB
11:07:43.22	DELTA	1.76 Hz	64.5 dB
11:07:43.38	THETA	5.57 Hz	63.8 dB
11:07:43.38	DELTA	1.76 Hz	63.8 dB
11:07:43.38	DELTA	1.46 Hz	63.8 dB
11:07:44.42	ALPHA	11.13 Hz	66.1 dB
11:07:44.93	ALPHA	10.84 Hz	57.4 dB
11:07:45.59	ALPHA	11.72 Hz	58.6 dB
11:07:46.47	ALPHA	9.38 Hz	52.7 dB
11:07:46.78	DELTA	2.64 Hz	47.3 dB
11:07:48.51	DELTA	1.76 Hz	41.7 dB
11:07:48.83	DELTA	1.46 Hz	49.3 dB
11:07:49.36	DELTA	1.17 Hz	42.8 dB
11:07:49.52	ALPHA	10.55 Hz	58.6 dB
11:07:50.55	ALPHA	9.67 Hz	59.8 dB
11:07:51.23	DELTA	3.81 Hz	53.8 dB
11:07:51.23	DELTA	3.52 Hz	53.8 dB
11:07:51.87	ALPHA	9.67 Hz	59.5 dB
11:07:53.27	DELTA	2.64 Hz	36.0 dB
11:07:53.61	DELTA	2.34 Hz	39.8 dB
11:07:53.96	DELTA	1.17 Hz	39.6 dB
11:07:54.12	DELTA	1.46 Hz	42.3 dB
11:07:54.30	DELTA	1.17 Hz	49.2 dB
11:07:58.39	DELTA	2.34 Hz	50.4 dB
11:07:58.74	DELTA	1.17 Hz	61.2 dB
11:07:59.43	DELTA	3.81 Hz	52.4 dB
11:07:59.74	DELTA	3.52 Hz	47.0 dB

LICENSE RESTRICTION: Valid for Technical Verification & Media Analysis. Void if used for Commercial Manufacturer Certification or Packaging Claims.

CRYPTOGRAPHIC SEAL (SHA-256): 8803d5b37b56954157662de6ac0841c676e445861830c3aa095fda1f1759fee3

Copyright © 2025-2026 Abundance Sea, LLC. All Rights Reserved. U.S. Patent No. 12,659,418; Patent Pending 19/660,467.
IND CORE™ Technology is ISO 17025:2017 Calibrated (Cert #05122C9A 2602).